

## RS485/RS232 CONVERTOR

Thingstels RS485/RS232 convertor Features 2 serial inputs and 1 alarm input & relay output, UC1152 supports standard LoRaWAN class C protocol, which is perfectly used as a remote data logger or a remote I/O controller. Coupled with a LoRaWAN gateway, UC1152 enables users to fastly build up a LoRa-Based IoT solution for data collection, remote control and monitoring of field devices.

### **SPECIFICATIONS:**

- Connector : 1 × 50 Ω SMA(Center PIN: SMA Female)
- Protocol : LoRaWAN 1.0/1.0.2 Class C
- Port : 1 × Micro USB Port
- Connector : Terminal block
- Digital Inputs : 2 x Opto-isolated Digital InputsDC Voltage (3-24V)
- Digital Outputs : 2 x SPDT Relay Contact Rating:3 Amp DC (Max: 30 V) or 3 Amp AC (Max: 250 V)
- Power Supply Input Voltage : 5-24V DC (Standard adapter: DC 12V/0.5A)
- Dimensions : 79 x 60 x 24 mm (3.11 x 2.36 x 0.94 in)
- Mounting : Desktop or Wall Mounting
- Reset Button : 1 × RESET (Inside The Device)
- LED Indicators : 1 × System, 1 × ACT
- Built-in : Watchdog
- Operating Temperature : -40°C to 70°C

